

EXHIBIT 3



09/369,570

DWPI

DERWENT-ACC-NO: 1991-371742

DERWENT-WEEK: 199812

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Stone building panel prodn. for flooring and walls - by laminating rear

surface of stone panel with fibre-reinforced plastic layer

PATENT-ASSIGNEE: MATSUSHITA ELECTRIC WORKS LTD[MATW]

PRIORITY-DATA: 1990JP-0043292 (February 23, 1990)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
JP 2714468 B2	February 16, 1998	N/A		E04F 013/14
JP 03247852 A	November 6, 1991	N/A		
				N/A

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
JP 2714468B2	N/A	1990JP-0043292
February 23, 1990		
JP 2714468B2	Previous Publ.	JP 3247852
N/A		
JP03247852A	N/A	1990JP-0043292
February 23, 1990		

INT-CL (IPC): B32B017/04; B32B019/00 ; E04F013/14

ABSTRACTED-PUB-NO: JP03247852A

BASIC-ABSTRACT: Stone building panel is prepd. by laminating the rear surface

of a natural or artificial stone panel with a fibre-reinforced plastic layer

prepd. by impregnating the plastic resin into chopped strand mat and cloth.

The reinforcement comprises the chopped strand mat in direct contact with the rear surface of stone panel and the cloth in a basis wt. ratio of 0.5-2.0 and has a total thickness of 0.5-2 mm. The filament is, e.g., glass fibre, polypropylene filament or carbon filament. The impregnating resin is, e.g., polyester, epoxy resin or acrylic resin. The FRP layer is formed by laminating the mat and cloth on the stone panel and coating the mat and cloth with the impregnating resin; or bonding the prepreg sheets on the rear surface of panel and hardening the resin; or laminating adhesively the FRP sheet on the rear

surface of the panel.

ADVANTAGE - The reinforcement has high toughness and bending strength and reduces the amt. of cloth used to provide economical reinforcement.

CHOSEN-DRAWING: Dwg.0/1

DERWENT-CLASS: A82 A93 G02 L02 P73 Q45

CPI-CODES: A12-R03; A12-R07; A12-S08F; G02-A05F; L02-D07;